



## D48022 0.8 - 2.2 GHz 4-Way Power Divider

### FEATURES

- ❖ Low Insertion Loss
- ❖ Low VSWR
- ❖ High Isolation
- ❖ Excellent Amplitude & Phase Tracking

### SPECIFICATIONS

0.8 – 2.2 GHz 4-Way Power Divider	
Model Number	D48022
Frequency Range	0.8– 2.2 GHz
Insertion Loss	0.5 dB Typ., 0.7 dB Max.
Isolation	25 dB Typ., 22 dB Min.
Input VSWR	1.15:1 Typ., 1.28:1 Max.
Output VSWR	1.10:1 Typ., 1.18:1 Max.
Amplitude Balance	0.08 dB Typ., 0.15 dB Max.
Phase Balance	0.8° Typ., 1.5° Max.
Power Handling As Divider	50 W CW
Connector Type	SMA Female
Impedance	50Ω Nom.
Operating Temperature	-55 °C To +105 °C

Note 1. Special requirement for small size and light weight unit available on request.

Note 2. Insertion loss refers to the sum of output power to the input power

Note 3. Amplitude and phase balance are RMS value of all the paths at any frequency

Note 4. Power handling is under the condition that all outputs are connected to the loads with 1.25:1 or better VSWR

