



D48061 0.8 - 1.6 GHz 4-Way Power Divider

FEATURES

- ❖ Low Insertion Loss
- ❖ Low VSWR
- ❖ High Isolation
- ❖ Excellent Amplitude & Phase Tracking

SPECIFICATIONS

0.8 – 1.6 GHz 4-Way Power Divider	
Model Number	D48061
Frequency Range	0.8– 1.6 GHz
Insertion Loss	0.5 dB Typ., 0.7 dB Max.
Isolation	24 dB Typ., 22 dB Min.
Input VSWR	1.15:1 Typ., 1.25:1 Max.
Output VSWR	1.15:1 Typ., 1.20:1 Max.
Amplitude Balance	0.08 dB Typ., 0.15 dB Max.
Phase Balance	1° Typ., 2° Max.
Power Handling As Divider	50 W CW
Connector Type	SMA Female
Impedance	50Ω Nom.
Operating Temperature	-55 °C To +105 °C

Note 1. Special requirement for small size and light weight unit available on request.

Note 2. Insertion loss refers to the sum of output power to the input power

Note 3. Amplitude and phase balance are RMS value of all the paths at any frequency

Note 4. Power handling is under the condition that all outputs are connected to the loads with 1.25:1 or better VSWR

