



Narrow Band SP7T

FEATURES

- ❖ Low Insertion Loss
- ❖ Low VSWR
- ❖ High Isolation
- ❖ TTL Compatible Logic
- ❖ Miniaturized Package Available
- ❖ Wide Operating Temperature Range

SPECIFICATIONS

Narrow Band SP7T						
Model Number	Frequency Range (GHz)	Insertion Loss (dB)	Isolation (dB)	Speed (ns)	VSWR	Type (R/S)
S7A1D82-100T100	1.8-2.0	1.1	100	100	1.3:1	A
S7A56-100T100	5-6	1.4	100	100	1.4:1	A
S7A1011-90T20	10-11	1.7	90	20	1.5:1	A
S7A1415-90T100	14-15	2.6	90	100	1.6:1	A
S7R2022-80T100	20-22	3.5	80	100	1.7:1	R
S7R2931-60T100	29-31	3.8	60	100	1.9:1	R
S7R3740-50T100	37-40	4.3	50	100	2.1:1	R

- Note 1. Type R is for Reflective switches and type A is for Absorptive switches.
 Note 2. DC requirement: +5 V at 420 mA, -5 V at -150 mA.
 Note 3. Miniaturized or customer outline package available on request.
 Note 4. Other customer electrical specification available on request.
 Note 5. TTL compatible logic control, Logic "0" on, "1" off. Binary logic control available on request.

